

AMENDMENTS TO THE CLAIMS

This listing of claims below will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1.(Currently amended) For use with a four-link hinge of the type typically used for closure of a vehicle movable deck such as a trunk lid or engine compartment hood, the hinge comprising a lower link bracket to be secured to the vehicle body, an upper link bracket to be secured to the movable deck, and pivoting links connected between the upper and lower brackets, an activating mechanism comprising:

(a) a driving arm having a proximal end and a distal end, the driving arm being pivotal about its proximal end,

(b) a driver configured to drive the driving arm about its proximal end,

(c) a track to be carried by the movable deck, and

(d) the distal end of the driving arm being coupled to the track, the distal end of the driving arm moves along the track ~~for movement therealong~~ as the driving arm is pivoted about its proximal end.

2.(Original) The invention of claim 1 wherein the driving arm is pivotal about an axis intersecting the lower bracket.

3.(Original) The invention of claim 2 wherein the lower link bracket provides the pivot axis for the proximal end of the driving arm.

4.(Original) The invention of claim 1 wherein the track comprises an extension of the upper link bracket.

5.(Original) The invention of claim 1 wherein the track is a channel and a bearing couples the distal end of the driving arm to the channel, the bearing being movable along the channel.

6.(Original) The invention of claim 1 wherein the driver is an electro-mechanical driver having an output shaft coupled to the proximal end of the driving arm and defining the axis about which the arm pivots.

7.(Original) The invention of claim 1 wherein the track is configured to be placed in the central region of the deck to extend in the longitudinal direction of the vehicle.

8.(Original) The invention of claim 7 wherein the driving arm proximal end is pivotally connectable to the central region of the vehicle and is generally in alignment with the track.

9.(Currently amended) A vehicle trunk lid or engine compartment hood closure mechanism comprising:

(a) four-link hinge comprising a lower link bracket to be secured to the vehicle body, an upper link bracket to be secured to the vehicle lid or hood, pivoting links connected between the upper and lower link brackets,

(b) a driving arm having a proximal end and a distal end, the driving arm being pivotal about its proximal end,

(c) a driver configured to drive the driving arm about its proximal end,

(d) a track to be secured to the lid or hood, and

(e) the distal end of the driving arm being coupled to the track, the distal end of the driving arm moves along the track ~~for movement therealong~~ as the driving arm is pivoted about its proximal end.

10.(Original) The invention of claim 9 wherein the driving arm is pivotal about an axis intersecting the lower bracket.

11.(Original) The invention of claim 10 wherein the lower link bracket provides the pivot axis for the proximal end of the driving arm.

12.(Original) The invention of claim 9 wherein the track comprises an extension of the upper link bracket.

13.(Original) The invention of claim 9 wherein the track is a channel and a bearing couples the distal end of the driving arm to the channel, the bearing being movable along the channel.

14.(Original) The invention of claim 9 wherein the driver is an electro-mechanical driver having an output shaft coupled to the proximal end of the driving arm and defining the axis about which the arm pivots.

15.(Original) The invention of claim 9 wherein the track is configured to be placed in the central region of the lid to extend in the longitudinal direction of the vehicle.

16.(Original) The invention of claim 15 wherein the driving arm proximal end is pivotally connectable to the central region of the vehicle and is generally in alignment with the track.

17.(Currently amended) A closure mechanism for opening and closing a vehicle trunk lid comprising:

(a) a driving arm having a proximal end and a distal end,

- (b) a driver having an output that moves about its axis,
- (c) a track to be secured to the trunk lid extending generally parallel to the longitudinal axis of the vehicle, and
- (d) the driving arm being pivotal about its proximal end relative to the vehicle and coupled to output of the driver, the distal end of the driving arm being coupled to the track, the distal end of the driving arm moves along the track ~~for movement therealong~~ as the driving arm is pivoted about its proximal end.

18.(Original) The invention of claim 17 wherein the track is a channel and a bearing couples the distal end of the driving arm to the channel, the bearing being movable along the channel.

19.(Original) The invention of claim 17 wherein the driver is an electro-mechanical driver having an output shaft coupled to the proximal end of the driving arm and defining the axis about which the arm pivots.